



3
Ph Output

INVERTERS

10 - 500 kVA



3 LEVEL
INVERTOR



TOWER



EASY
SERVICE



BATTERY
CONNECTION



MARITIME



MEDICAL



TRANSPORTATION



INDUSTRY



TELECOMMUNICATIONS

SPECIAL PRODUCTS

INVERTERS

INV series 3 phase output frequency inverters are digital microprocessors controlled products to run your mission critical equipment.

DC/AC Inverters provide quality energy for your critical loads by converting the voltage in the wide input voltage range (48-400 Vdc) to the desired voltage and frequency values with IGBT technology.

- 3-Level IGBT Technology
- Multiprocessor Digital Control
- 256 detailed real-time event logs
- Data analysis via the user panel
- Bypass option
- RS232, RS485 communication port and dry contact outputs
- Special production input-output values according to needs
- Models with 3-phase output
- SNMP compatible communication
- Remote monitoring and management software

INVERTERS INV SERIES

Input	
Voltage	48 / 96 / 110 / 220 / 400 Vdc (Optional)
Frequency	50Hz / 60Hz / 400Hz (±5%)
Output	
Power (kVA)	10 kVA - 500 kVA
Voltage	220 / 230 / 240 V 1PH+N+PE 50/60/400 Hz (other types special order)
Voltage Regulation	±1% (balanced load) ±2% (unbalanced load)
Frequency	50/60/400Hz
Frequency Stability	±2%Hz (free running)
Efficiency	≥ 90%
Overcurrent Protections	Electronic protection
Voltage Protection	Vac voltage low and high protection
THD of Output Voltage	≤2% (Linear load) & ≤5% (Non-linear load)
Load Power Factor	0.8 (0.9 and 1 optional)
General	
Power Module	IGBT
Font Panel	Alphanumeric or Graphical lcd screen, Led bar satatus
Control Buttons	5 buttons
Bypass	Available as option
Bypass Isolation	Available as option
Parallel Operation	Available as option
Alarm Buzzer	Available
Emergency Power Off (EPO)	Available
DC Input Protection	3 level alarms
Communication Ports (Optional)	RS485, Genset, SNMP, GSM Modem, Relay Contacts, Input Contacts, Modbus and USB
Battery Temprature Sensor Contact	Available
Remote Display	Available
Ambient Conditions	
Operating Tempature	0°C - 40°C
Storage Temperature	-15°C / +50°C
Proposed Temp. To Extend Battery Life	20 - 25°C
Relative Humidity (%)	<95% non condensing
Altitude	<1000m
Protection Class	IP20 (Higher IP Ratings are optional)

The company reserves the right to change specifications and designs without notice.



INNOVATIVE ENERGY SYSTEMS

www.innovasis.com.tr

The company reserves the right to change specifications and designs without notice.